

VERIFLO SERIES 600, MODELS 629 & 636

Quality Design Features Assure Long, Trouble-Free Service



WIDE RANGE OF APPLICATIONS:

- Industrial Spray Washer
- Pickling / Bonderizing
- Spray Booths
- Coolant Systems
- Filtration Systems
- Pollution Control
- E-Coat Paint Systems

CAPABILITIES:

- Capacities to 3000 GPM
- Heads to 230 Feet
- Temperature to 180° F
- Column Extensions of 12", 15" & 21"
- Construction: Cast Iron, 316 Stainless Steel Fitted, 316 Stainless Steel, Alloy 20

600

CONSTRUCTION:

Standard

- All iron construction
- Stress-Proof alloy steel shaft
- External impeller adjustment
- Cartridge type thrust bearing housing and cap
- Double row thrust bearing
- Semi-Open impeller with balancing ring and wiping vanes
- 12" flanged column extension
- Steel cover plate
- Schedule 40 discharge pipe
- Cast iron motor support
- Flexible coupling

Options

- Stainless steel fitted, All stainless steel or Alloy 20 construction
- Pump down feature
- Suction piping
- Column extension available for 15" or 21" extensions
- Oversize cover plates
- Fabricated steel chairs for "T" or "U" frame foot mounted motors

Shaft Sizes

Model Number 629.....2 1/4"
 Model Number 636.....2 1/2"