



**1. Power Frame**

Rugged heavy duty cast iron design incorporating integrally cast support and ribbed mounting feet which assure a solid, dependable pump installation and operation. One frame fits all pump sizes. External impeller adjustment is standard. Grease lubrication of bearings is standard; oil lubrication available.

**2. Bearings**

Series 1400 contains a high capacity cartridge-mounted double row thrust bearing allowing use on high suction pressure applications. Radial bearing is single row or double row and floats in a precision bored housing.

**3. Shaft**

416 stainless steel, precision machined with preferred taper at impeller location. Positive attachment is provided with castellated impeller nut and cotter pin, which assures that the impeller will not back off the shaft if the pump is accidentally operated in reverse rotation. 316 stainless steel shaft is optional.

**4. Shaft Sealing**

Packed arrangement utilizes a 2-piece split gland, slinger, Teflon® split lantern ring and 5-ring packing set. Grease lubrication is standard with product or water flush available. Wide choice of John Crane and Durametallic mechanical seals of various configurations and materials are optional.

E.I DuPont registered®

**5. Impeller**

Semi-open design which accommodates passage of solids or fines. All impellers have balance holes near the impeller hub which reduce thrust load and pressure in the packing or seal area. Wiping vanes reduce axial loading and prevent dirt from entering the sealing area. Impeller is keyed to shaft with a positive taper fit to assure perfect attachment.

**6. Impeller Adjustment**

Every power frame contains an external impeller adjustment utilizing jackscrews which provides for clearance adjustment between the impeller vanes' face and casing. This adjustment feature compensates for internal wear. Expensive casing and impeller wearing rings are eliminated.

**7. Casing**

High efficiency volute design. 4X3X10 and larger sizes are double volute, containing a splitter, which reduces bearing loading and shaft deflection; thus extending bearing and packing or mechanical seal life. All suction and discharge openings are flanged for installation ease and integrity.

**8. Back Pull-Out**

All pumps\* are designed with back pull-out feature which allows for removal of all pump rotating components without disturbing the piping connections. \*except size 2X1 1/2X12